



DISCHARGE REACTOR;
UN(V):690;
IEFF(A):0,02

General technical data:

product designation		discharging reactor
product brand name		SIDAC
Phase number		3
type of voltage		AC
Operating voltage / rated value		
• maximum	V	690
Operating frequency / rated value		
• maximum	Hz	0
Current		
• for AC / maximum	A	0.02

Mechanical design:

Design of the electrical connection / for main current circuit		screw-type terminals
Width	m	0.045
Height	m	0.09
Depth	m	0.06

Ambient conditions:

Thermal class / according to IEC 60085		B
Ambient temperature / rated value	°C	40

Protection class IP

IP00

Certificates/approvals:

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/4EJ9900-0EG/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=4EJ9900-0EG

last change:

Mar 4, 2013