SIEMENS

Data sheet 3UL2203-1B

Residual current protection device Component summation current transformer without ON delay Bushing opening 120 mm Rated fault current 6 A

General technical data	
product designation	summation current transformer for residual current monitoring
product feature touch protection	Yes
type of electrical connection at output	screw-type terminals
fault current at input rated value	6 A
reference code according to IEC 81346-2	B
reference code according to DIN 40719 extended according to IEC 204-2 according to IEC 750	K
reference code according to EN 61346-2	K
Ambient conditions	
ambient temperature	
● during operation	-20 ... +70 °C
Installation/ mounting/ dimensions	
diameter of inlet opening	120 mm
width	200 mm
height	85 mm
depth	200 mm
fastening method	screw fixing
Certificates/ approvals	

General Product Approval | **Test Certificates**

Type Test Certificates/Test Report | Special Test Certificate

Maritime application | **other** | **Environment**

Confirmation | Miscellaneous | Environmental Confirmations

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UL2203-1B
Cax online generator
https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UL2203-1B
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3UL2203-1B
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3UL2203-1B&lang=en

last modified: 9/17/2021

Subject to change without notice
© Copyright Siemens