OMRON Industrial Automation



G2R-2-SNDI 24VDC (S)

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, coil suppressor, lockable test button, label facility

Specifications

Mounting method	With plug-in socket
Usage	General purpose, Interface
Poles	2
Coil voltage	24 V
Rated carry current	5 A
Operation voltage	DC
Contact material	AgSnIn
Contact description	DPDT
Features	Diode, LED, Test button, Transparent case, With mechanical indicator
Terminal	Plug-in

Fits to



P2RF-08-PU
Socket, DIN rail/surface mounting, 15.5 mm, 8-pin, Push-in terminals



P2RF-08-S
Socket, DIN rail/surface mounting, 8-pin, screwless terminals

Downloads

CAD Library



EAC Mark removal

Discontinuation Notice

EN PDF 221 KB



G2R-_-S (S) General-purpose Relay

Datasheet

EN PDF 3.9 MB



Industrial Relays

Brochure

EN PDF 2.77 MB



OMRON Manufacturing Know-How: High Quality Relays

Leaflet

EN PDF 449 KB



Panel Building

Brochure

EN PDF 3.11 MB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 3 September, 2024. Click here for terms of use.