SIEMENS

Product data sheet 3UL2202-3A



RESIDUAL-CURRENT DEVICE COMPON.SUMMATION CURR.TRANSF. W/O PICK-UP DELAY WINDOW 65MM RTD.FAULT CURRENT 1A

General technical details:		
Item designation / according to DIN 40719 extendable after IEC 204-2 / according to IEC 750		K
Item designation / according to DIN EN 61346-2		K
Ambient temperature		
• during operating	°C	-20 … 70 …

Mechanical design:		
Diameter / of the feedthrough	mm	65
Conductor cross section that can be connected / of the terminal	mm²	2.5
Width	mm	125
Height	mm	70
Depth	mm	110

Certificates/approvals:

© Copyright Siemens AG 2013

General Product Approval			Test Certificates	
CSA	GOST	UL	Special Test Certificate	

Shipping Approval				other	
DNV	GL	LRS	RMRS	Declaration of Conformity	other

Further information:

Information- and Downloadcenter (Catalogs, Brochures,…)
http://www.siemens.com/industrial-controls/catalogs

Industry Mall (Online ordering system)
http://www.siemens.com/industrial-controls/mall

CAx-Online-Generator
http://www.siemens.com/cax

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
http://support.automation.siemens.com/WW/view/en/3UL2202-3A/all

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3UL2202-3A

last change: Jan 21, 2013

© Copyright Siemens AG 2013